



- 技术参数:
- 插芯:
- 插针数: 12/2+PE
 - 额定电流:
 - 电力区: 40A
 - 信号区: 10A
 - 额定电压:
 - 电力区: 690V
 - 信号区: 250V
 - 额定脉冲电压:
 - 电力区: 8kV
 - 信号区: 4kV
 - 污染等级: 3
 - 依据UL/CSA的额定电压: 600V/300V
 - 绝缘阻抗: $> 10^{10}\Omega$
 - 材料: 聚碳酸酯
 - 颜色: RAL 7032 (浅灰色)
 - 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - 依据UL 94的阻燃等级: V0
 - 可插拔次数: > 500
- 插针:
- 接线方式: 冷压连接
 - 材料: 铜合金
 - 表面处理:
 - 镀银
 - 镀金
 - 接触电阻:
 - 强电针: $< 0.3\text{m}\Omega$
 - 信号针: $< 3\text{m}\Omega$
 - 线径范围:
 - 强电针: $1.5-6\text{mm}^2(16-10 \text{ AWG})$
 - 信号针: $0.14-2.5\text{mm}^2(26-14 \text{ AWG})$
 - 工具:
 - 冷压钳:
 - 退针器:

- Technical specification:
- Insters:
- No. of contact: 12/2+PE
 - Rated current:
 - Power area: 40A
 - Signal area: 10A
 - Rated voltage:
 - Power area: 690V
 - Signal area: 250V
 - Rated impulse voltage:
 - Power area: 8kV
 - Signal area: 4kV
 - Pollution degree: 3
 - Rated voltage acc.to UL/CSA: 600V/300V
 - Insulation resistance: $> 10^{10}\Omega$
 - Material: polycarbonate
 - Colour: RAL 7032(light grey)
 - Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - Flammability acc.to UL 94: V0
 - Mating cycles: > 500
- Contacts:
- Terminal: crimp terminal
 - Material: copper alloy
 - Surface:
 - Hard-silver plated
 - Hard-gold plated
 - Contact resistance:
 - Power contacts: $< 0.3\text{m}\Omega$
 - Signal contacts: $< 3\text{m}\Omega$
 - Wire gauge:
 - Power contacts: $1.5-6\text{mm}^2(16-10 \text{ AWG})$
 - Signal contacts: $0.14-2.5\text{mm}^2(26-14 \text{ AWG})$
 - Tools:
 - Crimp contact tool:
 - Contact removal tool:

				订货号 Order No.
版本 REV	重量 weight	比例 Scale	产品代号 Part Code	
V1.0	82g	1:1	SO-HK-012/2-FC	


浙江思美克电气科技有限公司
 ZHEJIANG SMICO ELECTRICAL TECHNOLOGY CO.,LTD